

## Connecting sleeve 4kt B2000-8



Connecting sleeve for transition between PE foam bolt and light bolt, and to standard splicing.

### Stock programme:

1 Sleeve 2000-8, M16x60 (22x22)	14.0 Kg/100 pcs.
2 Sleeve 2000-8, M20x70 (30x30)	33.0 Kg/100 pcs.
3 Sleeve 2000-8, M24x80 (32x32)	38.0 Kg/100 pcs.
4 Sleeve 2000-8, M27x90 (40x40)	75.0 Kg/100 pcs.
5 Sleeve 2000-8, M16/M20x70 (30x30)	34.0 Kg/100 pcs.
6 Sleeve 2000-8, M16/M24x80 (32x32)	38.0 Kg/100 pcs.
7 Sleeve 2000-8, 1" UNCx80 (32x32)	38.0 Kg/100 pcs.

### Reference and weight:

- 1 PTC-005
- 2 PTC-005
- 3 PTC-005
- 4 PTC-005
- 5 PTC-005-3
- 6 PTC-005-3
- 7

Has the equivalent capacity to an 8.8 grade bolt of the same size.

See table for capacity calculations.

### Corrosion protection/Pc-Coat

Hot-dip galvanization is carried out in compliance with NS-EN-ISO 1461 and epoxy powder coating in compliance with NS-EN 13438. With regard to coating thickness and further information, please see Document Q/PTC-T19A – Specification for Pc-Coat – SVV/JBV.

Please also refer to the Pc-Coat Product Data Sheet and accompanying FDV documentation.

### Accessories:

Bolts and PE foam for light bolts